

Specifications

Anvil Trailer 7' Wide Tandem Axle				
Model	AT7X12TA	AT7X14TA	AT7X16TA	AT7X18TA
Overall Length	15'9"	17'9"	19'9"	21'9"
Width	8'6"	8'6"	8'6"	8'6"
Height	7'9" & 8'1" w/vent	7'9" & 8'1" w/vent	7'11" & 8'3" w/vent	7'11" & 8'3" w/vent
Interior Length	13'9"	15'9"	17'9"	19'9"
Width	6'9"	6'9"	6'9"	6'9"
Height	6'3"	6'3"	6'3"	6'3"
Rear Door Type	Ramp	Ramp	Ramp	Ramp
Width	6'3"	6'3"	6'3"	6'3"
Height	5'9"	5'9"	5'9"	5'9"
Hitch Weight	196 lbs	212 lbs	226 lbs	248 lbs
Height	15"	15"	17"	17"
Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Platform Height	18"	18"	20"	20"
G.A.W.R.	7000 lbs	7000 lbs	7000 lbs	7000 lbs
Curb Weight	1960 lbs	2120 lbs	2260 lbs	2480 lbs
Payload	5040 lbs	4880 lbs	4740 lbs	4520 lbs
Axles (Tandem)	3500 lbs	3500 lbs	3500 lbs	3500 lbs
Brakes	Electric	Electric	Electric	Electric
Tires	ST205/75R15C	ST205/75R15C	ST205/75R15C	ST205/75R15C
Wheels	Steel Silver Mod	Steel Silver Mod	Steel Silver Mod	Steel Silver Mod
Frame	4" Tube	4" Tube	6" Tube	6" Tube
Floor (16" OIC)	4" C-Channel	4" C-Channel	6" C-Channel	6" C-Channel
Sidewalls (16" OIC)	1" x 1½" Tube	1" x 1½" Tube	1" x 1½" Tube	1" x 1½" Tube
Standard Features				
<ul style="list-style-type: none"> * Ramp Rear Door * 24" ATP Stoneguard * Non Powered Roof Vent * Leaf Spring Axle * E-Z Lube Hubs w/Grease Caps * Silver Modular Wheels * 12 Volt Dome Light * Radial Tires * Galvanized Roof * ¾" Plywood Flooring * ⅜" Plywood Walls * Aluminum Fenders * Molded License Plate Holder w/Light * V-Nose Front * .024 Aluminum Exterior (Available in 6 Colors) * Colored Aluminum Wrap on Rear * Exposed Steel Painted Black * Undercoated Frame * Welded Safety Chains * Full-Color Decals * DOT Approved Lighting (L.E.D.)! * 32" x 68" Side Door w/Flushlock 				