

Specifications

Anvil Trailer 8' Wide Tandem Axle				
Model	AT8X14TA	AT8X16TA	AT8X18TA	AT8X20TA
Overall Length	18'5"	20'5"	22'5"	24'5"
Width	8'6"	8'6"	8'6"	8'6"
Height	8'5" & 8'9" w/vent	8'5" & 8'9" w/vent	8'5" & 8'9" w/vent	8'5" & 8'9" w/vent
Interior Length	16'4"	18'4"	20'4"	22'4"
Width	7'9"	7'9"	7'9"	7'9"
Height	6'6"	6'6"	6'6"	6'6"
Rear Door Type	Ramp	Ramp	Ramp	Ramp
Width	7'3"	7'3"	7'3"	7'3"
Height	6'0"	6'0"	6'0"	6'0"
Hitch Weight	260 lbs	280 lbs	300 lbs	320 lbs
Height	17"	17"	17"	17"
Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Platform Height	20"	20"	20"	20"
G.A.W.R.	7000 lbs	7000 lbs	7000 lbs	7000 lbs
Curb Weight	2600 lbs	2800 lbs	3000 lbs	3200 lbs
Payload	4400 lbs	4200 lbs	4000 lbs	3800 lbs
Axles (Tandem)	3500 lbs	3500 lbs	3500 lbs	3500 lbs
Brakes	Electric	Electric	Electric	Electric
Tires	ST205/75R15C	ST205/75R15C	ST205/75R15C	ST205/75R15C
Wheels	Steel Silver Mod	Steel Silver Mod	Steel Silver Mod	Steel Silver Mod
Frame	6" Tube	6" Tube	6" Tube	6" Tube
Floor (16" OIC)	6" C-Channel	6" C-Channel	6" C-Channel	6" C-Channel
Sidewalls (16" OIC)	1" x 1½" Tube	1" x 1½" Tube	1" x 1½" Tube	1" x 1½" Tube
Standard Features				
<ul style="list-style-type: none"> * Ramp Rear Door * 24" ATP Stoneguard * Non Powered Roof Vent * Leaf Spring Axle * E-Z Lube Hubs w/Grease Caps * Silver Modular Wheels * 12 Volt Dome Light * Radial Tires * Galvanized Roof * ¾" Plywood Flooring * ⅜" Plywood Walls * Aluminum Fenders * Molded License Plate Holder w/Light * V-Nose Front * .024 Aluminum Exterior (Available in 6 Colors) * Colored Aluminum Wrap on Rear * Exposed Steel Painted Black * Undercoated Frame * Welded Safety Chains * Full-Color Decals * DOT Approved Lighting (L.E.D.)! * 36" x 78" Side Door w/Flushlock 				