

Specifications

Anvil Trailer 8'6" Wide Tandem Axle (Con't)				
Model	AT86X26TA	AT86X28TA	AT86X30TA	AT86X32TA
Overall Length	30'6"	32'6"	34'6"	36'6"
Width	8'6"	8'6"	8'6"	8'6"
Height	8'3½" & 8'7½" w/vent	8'3½" & 8'7½" w/vent	8'3½" & 8'7½" w/vent	8'3½" & 8'7½" w/vent
Interior Length	28'	30'	32'	34'
Width	8'1"	8'1"	8'1"	8'1"
Height	6'6"	6'6"	6'6"	6'6"
Rear Door Type	Ramp	Ramp	Ramp	Ramp
Width	7'7½"	7'7½"	7'7½"	7'7½"
Height	6'3"	6'3"	6'5"	6'5"
Hitch Weight	380 lbs	400 lbs	420 lbs	440 lbs
Height	19"	19"	19"	19"
Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Platform Height	22"	22"	22"	22"
G.A.W.R.	9990 lbs	9990 lbs	9990 lbs	9990 lbs
Curb Weight	3800 lbs	4000 lbs	4200 lbs	4400 lbs
Payload	6190 lbs	5990 lbs	5790 lbs	5590 lbs
Axles (Tandem)	5200 lbs	5200 lbs	5200 lbs	5200 lbs
Brakes	Electric	Electric	Electric	Electric
Tires	ST225/75R15C	ST225/75R15C	ST225/75R15C	ST225/75R15C
Wheels	Steel Silver Mod	Steel Silver Mod	Steel Silver Mod	Steel Silver Mod
Frame	8" Tube	8" Tube	8" Tube	8" Tube
Floor (16" OIC)	8" C-Channel	8" C-Channel	8" C-Channel	8" C-Channel
Sidewalls (16" OIC)	1" x 1½" Tube	1" x 1½" Tube	1" x 1½" Tube	1" x 1½" Tube
Standard Features				
<ul style="list-style-type: none"> * Ramp Rear Door * 24" ATP Stoneguard * Non Powered Roof Vent * Leaf Spring Axle * E-Z Lube Hubs w/Grease Caps * Silver Modular Wheels * 12 Volt Dome Light * Radial Tires * Galvanized Roof * ¾" Plywood Flooring * ⅜" Plywood Walls * Aluminum Fenders 		<ul style="list-style-type: none"> * Molded License Plate Holder w/Light * V-Nose Front * .024 Aluminum Exterior (Available in 6 colors) * Beavertail Frame * Colored Aluminum Wrap on Rear * Exposed Steel Painted Black * Undercoated Frame * Welded Safety Chains * Full-Color Decals * DOT Approved Lighting (L.E.D.)! * 36" x 78" Side Door w/Flushlock * (4) Floor D-Rings 		