

Specifications

Anvil Trailer 6' Wide Single Axle				
Model	AT6X10SA	AT6X12SA	AT6X14SA	
Overall Length	13'9"	15'9"	17'9"	
Width	7'10"	7'10"	7'10"	
Height	7'8" & 8'0" w/vent	7'8" & 8'0" w/vent	7'8" & 8'0" w/vent	
Interior Length	11'5"	13'5"	15'5"	
Width	5'9"	5'9"	5'9"	
Height	6'3"	6'3"	6'3"	
Rear Door Type	Ramp	Ramp	Ramp	
Width	5'2½"	5'2½"	5'2½"	
Height	5'10"	5'10"	5'10"	
Hitch Weight	110 lbs	120 lbs	130 lbs	
Height	14"	14"	14"	
Ball Size	2"	2"	2"	
Platform Height	17"	17"	17"	
G.A.W.R.	2990 lbs	2990 lbs	2990 lbs	
Curb Weight	1100 lbs	1200 lbs	1300 lbs	
Payload	1890 lbs	1790 lbs	1690 lbs	
Axles (Single)	2990 lbs	2990 lbs	2990 lbs	
Brakes	Idler	Idler	Idler	
Tires	ST205/75R15C	ST205/75R15C	ST205/75R15C	
Wheels	Steel Silver Mod	Steel Silver Mod	Steel Silver Mod	
Frame	3" Tube	3" Tube	3" Tube	
Floor (24" OIC)	3" C-Channel	3" C-Channel	3" C-Channel	
Sidewalls (16" OIC)	1" x 1½" Tube	1" x 1½" Tube	1" x 1½" Tube	
Standard Features				
<ul style="list-style-type: none"> * Ramp Rear Door * 24" ATP Stoneguard * Non Powered Roof Vent * Leaf Spring Axle * E-Z Lube Hubs w/Grease Caps * Silver Modular Wheels * 12 Volt Dome Light * Radial Tires * Galvanized Roof * ¾" Plywood Flooring * ⅜" Plywood Walls * Aluminum Fenders 	<ul style="list-style-type: none"> * Molded License Plate Holder w/Light * V-Nose Front * .024 Aluminum Exterior (Available in 6 Colors) * Colored Aluminum Wrap on Rear * Exposed Steel Painted Black * Undercoated Frame * Welded Safety Chains * Full-Color Decals * DOT Approved Lighting (L.E.D.)! * 32" x 68" Side Door w/Flushlock 			